



Non contractual illustration

## ADVANTAGES

- New standard high adherence clamps with renewable spikes
- Vertical bead breaker with 3 different height settings
- Demounting/mounting tool equipped with an integrated alloy rim protection
- Helper and roller as original equipment fitted to simplify mounting operations
- Liberated pedal assembly to make operations easier
- Filter regulator lubricator included
- Powered by the LifePO4 battery on the **PCS-MICRO-LITHV4P-02** compressor (refer to the technical datasheet).
- Quick connection to the battery on the **PCS-MICRO-LITHV4P-02**.

This tyre changer and bead breaker are mounted on slides. This system allows the machines to be easily into and out of the vehicle for a working or storage position.

With the help of its slides equipped with stops and a kickstand, the machine is perfectly stable during use.

## STANDARD ACCESSORIES

Standard lever with an integrated alloy rim protection

## FEATURES

<b>POWER SUPPLY / AIR SUPPLY</b>	12 Vdc / 6-8 BAR (88-116 PSI)	<b>OUTSIDE CLAMPING CAPACITY</b>	10 ÷ 22"
<b>MOTOR RATED POWER</b>	1.6 kW	<b>INSIDE CLAMPING CAPACITY</b>	12 ÷ 24"
<b>WHEEL MAX. Ø *</b>	900 mm (35")	<b>BEAD BREAKING FORCE</b>	9700 N at 8 BAR (116 PSI)
<b>WHEEL MAX. WIDTH *</b>	300 mm (12")	<b>BEAD BREAKING OPENING *</b>	50 ÷ 300 mm (2 ÷ 12")
<b>TURNTABLE ROTATION SPEED</b>	9 rpm	<b>SOUND LEVEL</b>	< 70 dB(A) at 1 meter
<b>AUTONOMY</b>	30 tyres approx.	<b>DIMENSIONS * (folded)</b>	L. 940 x W. 1340 x H. 1165 mm
<b>CHARGING TEMPERATURE</b>	-15°C to 45°C	<b>DIMENSIONS * (unfolded)</b>	L. 940 x W. 2275 x H. 1165 mm
<b>DISCHARGE TEMPERATURE</b>	-15°C to 60°C	<b>NET WEIGHT *</b>	326 kg

\* Weights and dimensions are given as information only and are subject to change without prior notice.

## Contact us

Please contact us for information.

**By mail** vendite@fasep.it • **By phone** +39 055 8403126

**Address** Via Faentina, 96 - 50032 Ronta (Firenze) ITALY

